

I2C Bus Monitor - Model JI-216

File Setup Help

Msg #	Time	Dir	Addr	Hex Data	ASCII Data	P	Ex Time	Status
54	0 23:13:47.31	W	30	04 04 05 05 06 06 07 07	JJ --••	x	209.0	OK
55	0 23:13:47.31	R	30	08 08 09 09 00 00 01 01	☒	x	209.1	OK
56	0 23:13:47.31	W	31	02 02 03 03 04 04 05 05	⌈⌈⌋⌋	x	209.0	OK
57	0 23:13:47.31	R	31	06 06 07 07 08 08 09	--••☒	x	199.0	Frame Error
58								Trigger: Frame Error
59	0 23:13:47.31	W	32	00 00 01 01 02 02 03 03	⌈⌈⌋⌋	x	209.0	OK
60	0 23:13:47.31	R	32	04 04 05 05 06 06 07 07	JJ --••	x	209.0	OK
61	0 23:13:47.31	W	33	08 08 09 09 00 00 01 01	☒	x	209.1	OK
62	0 23:13:47.31	R	33	02 02 03 03 04 04 05 05	⌈⌈⌋⌋	x	209.0	OK
63	0 23:13:47.31	W	34	06 06 07 07 08 08 09 09	--••☒	x	209.1	OK
64	0 23:13:47.31	R	34	00 00 01 01 02 02 03 03	⌈⌈⌋⌋	x	209.0	OK
65	0 23:13:47.31	W	35	04 04 05 05 06 06 07 07	JJ --••	x	209.0	OK
66	0 23:13:47.31	R	35	08 08 09 09 00 00 01 01	☒	x	209.1	OK
67	0 23:13:47.31	W	36	02 02 03 03 04 04 05 05	⌈⌈⌋⌋	x	209.0	OK
68	0 23:13:47.31	R	36	06 06 07 07 08 08 09 09	--••☒	x	209.1	OK
69	0 23:13:47.31	W	37	00 00 01 01 02 02 03 03	⌈⌈⌋⌋	x	209.0	OK
70	0 23:13:47.31	R	37	04 04 05 05 06 06 07 07	JJ --••	x	209.0	OK
71	0 23:13:47.31	W	38	08 08 09 09 00 00 01 01	☒	x	209.1	OK
72	0 23:13:47.31	R	38	02 02 03 03 04 04 05 05	⌈⌈⌋⌋	x	209.0	OK
73	0 23:13:47.31	W	39	06 06 07 07 08 08 09 09	--••☒	x	209.1	OK

Operation: Run Stop

Timing Data: Sample CLK 40ns

Trace Mode: Streaming Trigger

BNC Output: Enabled

USB Port: Open Close

Time Div: uSec

Zoom All Zoom In Zoom Out

Sample CLK: 40ns Capture Time: 4/25/2010 11:13:56 PM

Status: Done Memory Count: 127K SDA: 1 SCL: 1 D0: 0 D1: 0 Bus Voltage = 3.3V USB: Open