

Incremental Encoder Emulator

Model JI-820

Jupiter Instruments

Ver 1.1

Electrical Specifications

1/20/2018 Edition

General				
Signals	A, /A, B, /B, Z, /Z			
Cycles per Revolution (CPR)	Programmable: 1 to 1,00,000			
Pulses per Revolution (PPR)	Programmable: 4 to 4,00,000			
Signal Phase Resolution	Selectable: 1, 5, 10, 45, or 90 degrees			
Frequency Range, Cycle	Phase Resolution	Freq. Max.	Freq. Min.	Resolution
	90	5.00 MHz	10.0 Hz	50 nS
	45	2.50 MHz	5.00 Hz	100 nS
	10	555 KHz	1.11 Hz	450 nS
	5	277 KHz	0.55 Hz	900 nS
	1	55.5 KHz	0.11 Hz	4500 nS
Position Tracking:				
Revolutions	-2 ³¹ to 2 ³¹			
Cycle	-2 ³¹ to 2 ³¹			
Phase	1 to 4			
Operational Modes	Free Run, Single-Step, Pulse Move			
Index Signal (Z)				
Position	Programmable: +/- 1 cycle span (max)			
Polarity	Selectable: Positive or Negative Pulse			
Output				
Type	Selectable: RS-422 Open-Drain Push-Pull Push-Pull Complementary			
Voltage Source	Internal or External			
Internal				
Voltage	Adjustable 5.0V to 18.0V (100mV increments)			
Current	Sink: 100 mA (max per signal) Source: 30 mA max per signal (90 mA combined)			
External				
Voltage	4.5V to 30.0V			
Current	Sink/Source: 100 mA (max per signal)			
Short-Circuit Protection	Internal and External			
Output Control	Enable/Disable Output			

Electrical Specifications (continued)

Connector:	
Type	Standard 9-Pin, D-sub, Female
Pin-outs	Pin 1 = External Voltage (Input) Pin 2 = Z Pin 3 = A Pin 4 = B Pin 5 = GND Pin 6 = GND Pin 7 = /Z Pin 8 = /A Pin 9 = /B
LEDs	
Power	Power-On
Activity	Output Signal Activity
PC Interface	
Communication	USB 2.0 Full Speed
Connector	Standard type B socket
Power	USB supplied Current Draw: 270mA (Nominal) 690mA (Maximum @ max. signal load)

Mechanical and Environmental Specifications

Mechanical	
Dimension	3.3" x 1.1" x 5.0" (WxHxL)
Weight	0.2lbs
Construction	Extruded Aluminum Enclosure
Environmental	
Operating Temp	0C to 45C
Storage Temp	-20C to 70C